



GLOBAL EAST ASIA TECHNOLOGY CO.,LIMITED

Product name:4 ports Panel Antenna

Product model:GL17270D32

4 ports Panel Antenna	
GL17270D32	
Electrical Specifications	
Frequency Range-MHz	2* 1710 - 2690MHz
Gain	20±dBi
VSWR	≤1.5
Polarization	2*±45°
Horizontal beam width	32±5°
Vertical beam width	8±2°
Horizontal Beam Direction	- 30°, +30°
Horizontal side lobe suppression	≥16dB
Front-to-back ratio-dB	≥25dB
Isolation	≥28dB
Intermodulation	≤ - 107dBm@2×43dBm
Input Impedance-Ω	50Ω
Maximum input power-W	300W
Input connector type	4×4.3 - 10 Female
Lightning protection	DC Ground
Mechanical Specifications	
Dimensions =height/width/depth	1200×500×200mm
Packing size	1275×564×295mm
Antenna weight	12.5±0.3Kg
Rated Wind Velocity	36.9m/s
Operating Humidity	10-95%
Radome Color	gray
Radome material	FRP
Operating Temperature	-30 - 65°C
Installation Method	pole- mounting
Mounting hardware	Φ35 - Φ90mm
Mechanical tilt	0 - 10°



Add: Room 826, Block B,BLDG 18, University Science Park(East), Zhengzhou City,P.R.Henan,China.
Tel: 86-371-60911368 Email:info@global-antenna.com
Web:<http://www.asialeren.com> <http://www.global-antenna.com>